## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

11-218468

(43) Date of publication of application: 10.08,1999

(51)Int.CI.

GO1M 11/02

(21)Application number: 10-331593

(71)Applicant: TOPCON CORP

(22)Date of filing:

20.11.1998

(72)Inventor: OTOMO FUMIO


NAKAMURA SHINICHI

## (54) LENS METER

## (57)Abstract:

PROBLEM TO BE SOLVED: To accurately and rapidly measure a refractive power even in the case of a progressive multiple-focus lens of unclear origine by measuring refractive characteristics at the different site of a lens to be inspected and storing the obtained refractive characteristic value along with position coordinates of a measurement site.

SOLUTION: An X-axis motor 12M, a Y-axis motor 11M, and a marking traveling motor 30M are connected to a pulse driver circuit 200. An initial control circuit 204 for controlling the retention of a lens to be inspected and the initial retention and positioning of the frame of glasses, a comparison circuit 206, a refractive characteristic measurement value processing part 207 for determining the refractive characteristics of the lens to be inspected based on information from a detector 1, a RAM 211, and a program memory 213 are connected to a sequencer 203, and then a display 208 is connected thereto. The RAM 211 is connected to the comparison



circuit 206, an operation circuit 209, the sequencer 203, and the initial control circuit 204. A ROM 212 is connected to the operation circuit 209 and the initial control circuit 204.

## **LEGAL STATUS**

Date of request for examination

24.11.1998

Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

3115280

[Date of registration]

29.09.2000

[Number of appeal against examiner's decision

of rejection]

[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office